

CONTINENTAL HYDRAULICS

CO5MSV-P*

PILOT OPERATED CHECK VALVE





CO5MSV-P* PILOT OPERATED CHECK VALVE





DESCRIPTION

This valve utilizes a guided spool and poppet-seat check valves as a blocking or load-holding device for high pressure applications.


OPERATIONS


This valve allows free flow from the directional control valve work port to the load and blocks flow in the opposite direction. Flow is allowed from the load to the directional control valve work port when 40% of the load induced pressure is sensed in the opposing directional control valve work port.


TYPICAL PERFORMANCE SPECIFICATIONS

MAXIMUM OPERATING I	PRESSURE	4600 psi	320 bar		
CRACKING PRESSURE		30 psi	2 bar		
MAXIMUM FLOW RATE		32 gpm	120 l/min		
PILOT RATIO		2.3:1			
DECOMPRESSION RATIO		14.9 : 1			
MOUNTING SURFACE		NFPA D05 ISO 4401-05-04-0-05			
WEIGHT	CO5MSV-PC	4.9 lbs	2.2 kg		
	CO5MSV-PA -PB	4.2 lbs	1.9 kg		

AVAILABLE VERSIONS








C05MSV-PB


C05MSV-PC



IDENTIFICATION CODE



PERFORMANCE CURVE





VALVE -	FLOW CURVE NUMBER					
	A1→A	B1→B	P→P1	T→T1	A→A1	B→B1
CO5MSV-PA	4	4	1	1	2	-
C05MSV-PB	4	4	1	1	-	2
C05MSV-PC	4	4	1	1	3	3

NOTE:

Values obtained with oil viscosity of 170 SUS (36 cSt) at 122°F (50°C).

DIMENSIONS





SEAL KIT

BUNA SEAL KIT	1013665
VITON SEAL KIT	1013666

Mounting surface with sealing rings: 5 O-Ring type AS568-014 - 90 shore A

ABOUT CONTINENTAL HYDRAULICS

Rugged, durable, high-performance, efficient—the reason Continental Hydraulics' products are used in some of the most challenging applications across the globe. With a commitment to quality customer support and innovative engineering, Continental's pumps, valves, power units, mobile and custom products deliver what the markets demand. Continental has been serving the food production, brick and block, wood products, automotive and machine tool industries since 1962. Learn how our products survive some of the most harsh environments.

SALES@CONTHYD.COM

5505 WEST 123RD STREET · SAVAGE, MN 55378-1299 / PH: 952.895.6400 / FAX: 952.895.6444 / WWW.CONTINENTALHYDRAULICS.COM

CONTINENTAL HYDRAULICS.